Product Data Sheet



GlassGuard Blackband® T5 LED Lamps



Product description

T5 LED high frequency retrofit high output energy efficient lamp with a high temperature chemical resistant fluoropolymer coating applied externally to retain glass and plastic fragments in the event of accidental breakage.

Maximise return on investment

- Ultra long service life T5 LED tubes (up to 60,000 hour/6.9 years) ensure maximum luminaire lifetime as they can be replaced
- Most integrated LED (strip or board) luminaires do not have replaceable components and require removal, repurchase and installation
- A cost-effective way to upgrade your luminaires

Product features

- Single BlackBand® ring marking
- Coated to a recognized industry standard EN61549
- Suitable for open and enclosed luminaire operation between -30°C and +40°C ambient (brand dependent)
- 99% visible light transmission through coating
- Coating FDA compliant to 21CRF177.1550 for food contact
- Coating passes EN 60598-1 850°C glow wire and needle flame tests
- Lamp and coating can be recycled
- Lamp coating process certified to ISO 9001:2008 quality management system and major lamp
 OEM supplier approvals
- Coating service temperature range -70°C to +200°C
- RoHs compliant

Product benefits

- Very high light output allowing for reduced numbers of luminaires, reduced capital cost and reduced payback periods
- Rated to 60,000 hours (6.9 years brand dependent) service life, significantly reducing maintenance costs
- Significantly reduces the risk of glass and plastic contamination and shedding of particles which can be difficult to detect
- BlackBand® ring marking allows fast identification during food safety management system audits
- Coating inert to all acids and alkalis
- Lamp can be cleaned and washed when used in GlassGuard® IP65 open-rated luminaire

Applications

- Suitable for standard and aggressive environments where cleaning chemicals are present*
- Ideal for cold-room storage

*Luminaire dependent

MSDS (Material Safety Data Sheet) available.

Lamps must be replaced at the end of their rated life.

All products where applicable are subject to WEEE recycling charge.









GlassGuard BlackBand® T5 LED Lamps



Length	Wattage	Colour	Service Life (hours)
5ft / 1449mm	25/26/37w	840/865	50,000/60,000

Beam angle 160°

Note: Wattage, lumen outputs and operating temperatures vary with brand. Please contact your local Lighting Advisor for advice on the right product for your environment.





